


Micro Seri Line Interactive UPS 600~3000VA



DELTA Line Interactive UPS özellikle ev ve ofis uygulamalarınıza çözüm sunabilecek mikroişlemci kontrolü, akıllı akü yönetim sistemine sahip kesintisiz güç kaynağıdır. Küçük hacmi ve şık tasarımı, LED/LCD ekran seçenekleri, USB ve RJ11 bağlantısı ile kullanımınıza sunulmuştur. Yüksek akım, Kısa devre, aşırı yük, yüksek akü şarj/ deşarj korumaları sayesinde güvenli bir kullanım imkanı sunar

Features

- Küçük hacim
- Opsiyonel dokunmatik LCD ekran
- USB ve RJ11 bağlantısı (opsiyonel)
- İleri teknoloji AVR (otomatik voltaj regülasyonu) kararlı çıkış gerilimi sağlar
- Yüksek güvenilirliği garanti eden mükemmel mikroişlemci kontrolü
- AC kurtarılrken yeniden başlatma özelliği
- Simüle sinüs dalga çıkış formu
- Kapalı konumda bile akü şarj özelliği
- Aküden başlama özelliği (cold start)



TEKNİK ÖZELLİKLER:



MODEL	MICRO600	MICRO800	MICRO1000	MICRO1200	MICRO1500	MICRO2000	MICRO2400	MICRO3000
Capacity (VA/Watts)	600/360	800/480	1000/600	1200/720	1500/900	2000/1200	2400/1440	3000/1800
INPUT								
Voltage	220/230/240vac							
Voltage Range	162-290vac							
Frequency Range	50/60Hz (auto sensing)							
OUTPUT								
AC voltage	220/230/240vac							
Regulation (Batt. Mode.)	±10%							
Frequency Range (Batt mode)	50/60Hz ± 1Hz							
Transfer Time	Typical 4-8ms, 13ms Max.							
Waveform(Batt mode)	simulated sine wave							
BATTERY								
BATTERY Voltage	12vdc		24vdc				48vdc	
Battery type&Number	7Ah x 1	9Ah x 1	Ah x 2	7Ah x 2	9Ah x 2	9Ah x 2	7Ah x 4	9Ah x 4
Typical Recharge Tim	6 - 8 hours (to 90% of full capacity)							
INDICATORS								
LED Display(LED Version)	AC Mode,Battery Mode,overload,fault							
LED Display(LED Version)	AC Mode,battery mode,load level,battery level , input voltage,output voltage,overload fault,and battery low							
PROTECTION								
Full protection	short circuit,overload,overcharge and overdischarge protection							
ALARM								
BATTERY mode	sounding every 10 seconds							
low battery	sounding every seconds							
overload	sounding every 0.5 seconds							
battery replacement	sounding every 2 seconds							
Alarm	continuously sounding							
Fault	continuously sounding							
MANAGEMENT	(Support windows 2000/2003/XP/Vista/2008,windows 7, Linux, Unix, and MAC)							
Communication port	USB or RS232							
OPERATING ENVIRONMENT								
Humidity	0-90%RH @0-40C(non-condensing)							
Noise level	Less than 45dB				Less than 55dB			
PHYSICAL								
Dimension D*W*H(mm)	298*101*142		353*149*162		380*158*198		433*144*207	
Net weight (kgs)	4.3	4.9	7.8	8.4	10.1	10.5	20	23
STANDARDS								
Dimension D*W*H(mm)	IEC/EN62040-1 ; IEC/EN60950-1							
Net weight (kgs)	IEC/EN62040-1; IEC61000-4-2 ; IEC61000-4-3 ; IEC61000-4-4 ; IEC61000-4-5 ; IEC61000-4-6 ; IEC61000-4-8							



DELTA ELECTRONIX DIŞ TİCARET LİMİTED ŞİRKETİ

Address: çağlayan mahallesi vatan caddesi no: 79/20 Elmaz İş Merkezi 3.Kat - istanbul – TURKEY

Tel: +90 535 554 10 26 Website: www.deltaelectronix.com, Email: info@deltaelectronix.com